



1 Ton - 3 Ton Mini Excavator Trailers Silver Tandem Axle Plant Trailer

Our Product Introduction

for more products please visit us on tippers-trailers.com

Basic Information

- Place of Origin: China
- Certification: 9001/TS 16949、CCC、CE、ADR、DOT
- Minimum Order Quantity: 1 Certification
- Delivery Time: 20-30 work days
- Payment Terms: L/C,D/A,T/T,D/P
- Supply Ability: Annual output :2000



Product Specification

- Name: Mini Excavator Trailers
- Trailer Dimensions: 4870*1900*2100mm(Trailer Ladder1600mm)
- Drawbar: 150*50*3 .2150 Long
- Internal Dimensions: 2230*1400*500mm
- Surface Treatment: Hot-dip Galvanizing
- Fully Welded Body & Chassis: Yes
- Color: Silver
- Light: LED ADR Light
- ATM: 3000kg
- Guide Wheel: 8 Inch
- Patterned Panel: 2.5 Pattern
- Spring: 8 Pieces
- Beam: 80*40*3
- Tire: 185R14LT



More Images



Product Description

Excavator trailer

Designed specifically for small excavators weighing 1-3 tons, it focuses on the needs of short-distance transportation and narrow road conditions on construction sites, and is the preferred partner for the transportation of small engineering equipment with the core of "corrosion-resistant, strong load-bearing, and easy operation".

The body adopts the overall hot-dip galvanizing process, which is treated with pickling to remove rust, high-temperature zinc plating, and passivation. The zinc layer has strong adhesion and is uniform and dense. It can resist the erosion of rain, soil, and acid-base environment. It does not rust when stored outdoors in the open air, and its service life is more than 3 times longer than that of ordinary spray-painted trailers. The frame is made of high-strength steel according to national standards, with an extra-thick load-bearing bottom plate. The overall load-bearing is stable and does not deform, and the rated load is fully compatible with small excavators, loaders, and other equipment.

Design to meet practical needs: the rear of the vehicle is equipped with reinforced double ladders, three ribs anti-slip design + double spring reinforcement, gentle slope angle, excavator up and down stable and non-slip; A 1200-pound manual/electric winch can be optionally installed, allowing one person to complete the loading and unloading of heavy loads. The body adopts a compact size design (commonly 2.1-25m long, 1.3-15m wide), and can flexibly navigate on rural roads and construction site alleys, with no pressure when turning or reversing.

Trailer dimensions:4870*1900*2100mm(Trailer ladder1600mm)
Drawbar:150*50*3 .2150 long
Internal dimensions: 2230*1400*500mm
Surface treatment: Hot-dip galvanizing
Fully Welded Body & Chassis: yes
Color: Silver
Light: LED ADR light

Our Product Introduction

ATM: 3000kg
Guide wheel:8 inch
Patterned panel:2.5 Pattern
Spring: 8 pieces
Beam: 80*40*3
Tire: 185R14LT
Swing wheel: 8 inches, operable
Brake: 10 inches, dual-axis electric brake
Plug:7 Pin, Flat/ Small Round/ Big Round
Certification:9001/TS 16949,CCC,CE,ADR,DOT

for more products please visit us on tippers-trailers.com



Liaocheng Liao zhuan Heavy Industry Machinery Co., Ltd.



+86 15206359222



Liaogong592@gmail.com



tippers-trailers.com

Shandong Liaocheng Guanxian Dianzi Liao zhuan Heavy Industry.